

# CLIMAFLEX PE ISOLERING

41

## ISOLERING TIL VVS ANLÆG



Isoleringstykkelse 9 mm				Isoleringstykkelse 13 mm			
Artikelnr	Dimension	m/ kart.	DKK/ meter	Art. nr.	Dimension	m/ kart.	DKK/ meter
3603909015	09 x 15	380	10,00	3603913015	13 x 15	256	14,95
3603909018	09 x 18	330	10,93	3603913018	13 x 18	220	15,97
3603909022	09 x 22	250	12,98	3603913022	13 x 22	180	16,92
3603909028	09 x 28	190	14,95	3603913028	13 x 28	140	21,95
3603909035	09 x 35	150	22,89	3603913035	13 x 35	120	27,85
3603909042	09 x 42	110	25,89	3603913042	13 x 42	90	37,85
3603909048	09 x 48	90	32,89	3603913048	13 x 48	70	49,82
3603909054	09 x 54	70	39,85	3603913054	13 x 54	66	54,75
3603909060	09 x 60	66	44,85	3603913060	13 x 60	48	59,82
3603909076	09 x 76	48	65,05	3603913076	13 x 76	40	79,00
3603909089	09 x 89	40	76,65	3603913089	13 x 89	30	99,83
3603909108	09 x 108	24	99,45	3603913108	13 x 108	22	118,70
3603909114	09 x 114	24	115,75	3603913114	13 x 114	22	129,35

Vi tager forbehold for fejl

Isoglobal, Rellerriege 26, DE-33161 Hövelhof  
[www.isoglobal.dk](http://www.isoglobal.dk)

# CLIMAFLEX PE ISOLERING

42

## ISOLERING TIL VVS ANLÆG



Isoleringstykkelse 20 mm			
Artikelnr	Dimension	m/ kart.	DKK/ meter
3603920015	20 x 15	134	29,90
3603920018	20 x 18	126	31,85
3603920022	20 x 22	108	33,85
3603920028	20 x 28	96	43,85
3603920035	20 x 35	70	49,82
3603920042	20 x 42	60	59,80
3603920048	20 x 48	48	76,75
3603920054	20 x 54	48	79,75
3603920060	20 x 60	40	89,65
3603920076	20 x 76	26	105,36
3603920089	20 x 89	24	136,25
3603920108	20 x 108	20	156,85
3603920114	20 x 114	14	185,97

Vi tager forbehold for fejl

Isoglobal, Rellerriege 26, DE-33161 Hövelhof  
[www.isoglobal.dk](http://www.isoglobal.dk)



Tekniske egenskab	Resultat	Testmetode
Cellestruktur	Lukketcellet	
Anvendelsestemperatur	fra 0° C - +100° C	EN 14707
Varmeledningsevne	≤ 0,040 W/ m·K ved +40° C	DIN EN ISO 8497
Brandklasse	6 mm - 25 mm BL, S1, d0	DIN EN 13501-1
	30 mm BL, S3, d0	